



## Remote Microphone Model 61-95039A-V2

Ideal for work vehicles operating on railroad tracks as well as land-based installations

### Features

- Enables user transmission over a 2-way radio from remote location
- Can be used in conjunction with Icom, Kenwood, and Motorola radios as well as LMG Speaker Switch 17-95160 and 17-95161
- Allows work crews access to the radio without needing to return to cab, providing additional safety when cab is in difficult to reach places
- When used in conjunction with a speaker switch box, the microphone connection is isolated, preventing loading to the radio microphone circuit

### Specifications

- Stores in a rugged, outdoor, all-steel enclosure measuring 8" x 6" x 4"
- Quick release latches and provision for padlock on casing
- LED is visible when PTT switch is actuated
- 30 feet of cable allows user to interface Remote Microphone to a mobile radio, additional cable length available on request
- Integral DTMF keypad
- Microphone output level: adjustable from 190 mV to 2300 mV

### Ordering Reference

61-95039A-V2 Remote Microphone\*

The Remote Microphone is typically mounted at the rear of a work truck and provides a second position from which to transmit over the vehicle's mobile radio.

\*When using with radio requiring very low level microphone input (e.g. Kenwood NX-700), a remote speaker switch is recommended.

17-95160, 17-95161 Remote Speaker Switch

The Remote Speaker Switch includes U-shaped mounting bracket and 3.5 mm plug with cord.