

LOCOMOTIVE SPEAKER PANEL Model 61-95035



Application:

The 61-95035 Locomotive Speaker Panel allows the operator to communicate over a locomotive's Clean Cab radio. The panel uses high-level audio from the radio's Auxiliary Connector, providing a volume control for the operator's convenience. A standard AAR-type 6-pin connector on the front panel accommodates a hand-held microphone.

Features and Operation:

- Rugged metal construction. Front panel fabricated of 16 ga. steel sheet
- Receives high-level radio receive audio from pins M & N of Clean Cab radio's Auxiliary Connector
- Speaker volume control
- Heavy duty, water-resistant 4" speaker
- 18" interface cable to connect to locomotive wiring. Can be directly connected to the Clean Cab radio with optional cable (see below for cable ordering reference).
- AAR-type 6-pin connector on front panel for hand held microphone (note: does not support handset)
- Size:
 - Overall – 6" x 8" x 1 5/8"
 - Bolting pattern – 5" x 7"
 - Back box – 4.25" x 6.03" x 1.55"

Ordering Information:

- 61-95035 Locomotive Speaker Panel with Microphone Connector
- 61-98014-X Cable to connect 61-95035 Panel directly to Auxiliary Connector of Clean Cab Radio. "X" denotes cable length; specify as needed.
- 61-55060A – Mounting Box – Facilitates mounting of Speaker Panel where "built-in" mounting is not feasible.